



Quality Speaks Itself..

PERFORMANCE CHART 3" SLIM PUMPSET

| | | | | | | |
|-----------------------------|--|---------------------------------|--------------------------------|------------------------------|--|--|
| Group Radial Flow | Bowl & Impeller Modified PPO Noryl | Rotor EC Grade Copper | Version Single Phase | Volt 220 Volt 50Hz | Outer Diameter Motor -74mm Pump -68mm | Suitable for 80 mm & above Dia.Borewell |
|-----------------------------|--|---------------------------------|--------------------------------|------------------------------|--|--|

Max. Head Per Stage 4 mtr.(13 feet) ● Duty Point Head 2.5 mtr. ● Outlet (NRV) - 32mm (1.25")

| (C-5) | DISCHARGE IN L.P.M. | | | 10 | 20 | 25 | 30 | 35 | 40 | 45 |
|-------------|---------------------|------|-----|----------------------|----|----|----|----|----|----|
| | Model | H.P. | STG | Total Head in Meters | | | | | | |
| | A13 - 50510 | 0.5 | 10 | 35 | 30 | 27 | 25 | 20 | 15 | 10 |
| A13 - 57515 | 0.75 | 15 | 53 | 45 | 41 | 38 | 30 | 23 | 15 | |
| A13 - 5120 | 1 | 20 | 70 | 60 | 54 | 50 | 40 | 30 | 20 | |
| A13 - 51525 | 1.5 | 25 | 88 | 75 | 68 | 63 | 50 | 38 | 25 | |

Max. Head Per Stage 4 mtr.(13 feet) ● Duty Point Head 2.5 mtr. ● Outlet (NRV) - 32mm (1.25")

| (C-7) | DISCHARGE IN L.P.M. | | | 15 | 25 | 30 | 35 | 40 | 50 | 60 |
|-------------|---------------------|------|-----|----------------------|----|----|----|----|----|----|
| | Model | H.P. | STG | Total Head in Meters | | | | | | |
| | A13 - 7058 | 0.5 | 8 | 28 | 24 | 22 | 20 | 16 | 12 | 8 |
| A13 - 77512 | 0.75 | 12 | 42 | 36 | 32 | 30 | 24 | 18 | 12 | |
| A13 - 7115 | 1 | 15 | 53 | 45 | 41 | 38 | 30 | 23 | 15 | |
| A13 - 71520 | 1.5 | 20 | 70 | 60 | 54 | 50 | 40 | 30 | 20 | |

Max. Head Per Stage 4 mtr.(13 feet) ● Duty Point Head 2.5 mtr. ● Outlet (NRV) - 32mm (1.25")

| (C-10) | DISCHARGE IN L.P.M. | | | 20 | 30 | 40 | 45 | 50 | 60 | 70 |
|--------------|---------------------|------|-----|----------------------|----|----|----|----|----|----|
| | Model No. 10 No | H.P. | STG | Total Head in Meters | | | | | | |
| | A13 - 1055 | 0.5 | 5 | 18 | 15 | 14 | 13 | 10 | 8 | 5 |
| A13 - 10757 | 0.75 | 7 | 25 | 21 | 19 | 18 | 14 | 11 | 7 | |
| A13 - 10110 | 1 | 10 | 35 | 30 | 27 | 25 | 20 | 15 | 10 | |
| A13 - 101515 | 1.5 | 15 | 53 | 45 | 41 | 38 | 30 | 23 | 15 | |

